



18W LED Driver

產品型號 Model	功率 W Power W	輸出電壓範圍 Output voltage range	輸出電流範圍 Output Current range	功率因數 Power Factor	定電壓/定電流 Constant voltage / constant current	產品壽命 Product life MIL-HDBK-217F(25°C)
NDN-1324-0700	17W	13~24V	700mA	0.6	CC&CV	20000Hrs
NDN-24-0700	17W	24V	0~0.7A	0.6	CV	20000Hrs
NDN-2536-0500	18W	25~36V	500mA	0.6	CC&CV	20000Hrs
NDN-36-0500	18W	36V	0~0.5A	0.6	CV	20000Hrs
NDN-3748-0350	17W	37~48V	350mA	0.6	CC&CV	20000Hrs
NDN-48-0350	17W	48V	0~0.35A	0.6	CV	20000Hrs

INPUT	VOLTAGE RANGE	90~264VAC
	FREQUENCY RANGE	47~63Hz
	POWER FACTOR	PF ≥ 0.6
	EFFICIENCY	>70%
	AC CURRENT	0.18A/110VAV / 0.10A/220VAC
	INRUSH CURRENT	40A / 230VAC
PROTECTION	OVER CURRENT	95~115% Protection type : Constant current limiting, recovers automatically after fault condition is removed
	SHORT CIRCUIT	Hiccup mode, recovers automatically after fault condition is removed
ENVIRONMENT	WORKING TEMP	-10~+40°C
	STORAGE TEMP	-20~+80°C
OTHERS	MTBF	20Khrs. MIL-HDBK-217F(25°C)
	DIMENSION	98mm (L)x36mm (W)x35mm (H)
	PACKING	